## **Ditch Section D2-Typical Sections for UNDERDRAIN PIPE 6" PERFORATED** POLYVINYL CHLORIDE 3/4" STONE GEOTEXTILE NON-WOVEN "C" STONE Underdrain FABRIC (not to scale) CWINININ (4" NINININ (M) -5% SLOPE **Road Section** 5" X 18" GRANITE CLASS B CONCRETE) (3000 psi) GBOTEXTILE FABRIC UNDERDRAIN PIPE 6" PERFORATED NON-WOVEN POLYVINYL CHLORIDE 3/4" STONE 8" OF 1½" CRUSHED BANK RUN GRAVEL 1" OR 1½" WEARING COURSE 2" OR 2½" BINDER COURSE GRAVEL (6" minus) 16" BANK RUN

G\Land Projects\E Standards\dwg\DPW D2 Underdrain Detaildwg 3/6/2007 81452 AM EST

NOTE: THESE STANDARDS ARE TO BE CONSIDERED AS MINIMUM REQUIREMENTS. ANY DEVIATION FROM THESE STANDARDS WILL REQUIRE THE LACONIA DEPT. OF PUBLIC WORKS APPROVAL.

(WITH CURB)

27 Bisson Avenue Laconia, NH 03246

Department of Public Works

Phone: 603-528-6379 Fax: 603-527-1298 CONT ON THE LAKES